

OPTIGRÜN RSA 40FO

Downspout Edge Inspection Chamber

Chamber for the discharge of water from downspouts with vertical outlet into drainage and retention layers.



Material	Aluminium
Colour	Aluminium natural
Material thickness	2 mm
Dimensions	L 400 x W 400 mm Base part floor area: L 560 x W 490 mm Height of chamber base part with inlet element: 200 mm can be raised in 50 mm and 100 mm increments
Discharge capacity	20 l/s (intermediate floor)
Quantity/delivery unit	Chamber base part, inlet element and intermediate floor incl. fastening material Without cover
Delivery form	according to size of order by parcel shipment or by forwarding agent
Pack size	according to size of order
Delivery weight	approx. 3.2 kg/piece

Area of use

- On downspouts with vertical outlet without bend
- To fit downpipes for the inlet and discharge of water from higher roof areas

Specific properties

- Inlet element with open top
- Can be combined with a cover with downspout inlet (Item No. 31902)
- To protect against splashing water and to reduce noise, install the cover
- Intermediate floor with 5 mm round perforation
- Revision possible through removable intermediate floor
- Connection options for 6 Optigrün Water Conduction Channels WKA or 9 Optigrün Water Conduction Channels WKK
- With rivet nuts, holes and screws for fastening the chamber components
- Insensitive to humic acids
- Load capacity in combination with Optigrün Downspout Inspection Chamber Cover DSA 40FO approx. 800 kg

Accessories

- Downspout Inspection Chamber Cover DSA 40FO: Item No. 31902
- Inspection Chamber Extension ASA 40-5 (50 mm): Item No. 31905
- Inspection Chamber Extension ASA 40-10 (100 mm): Item No. 31906

The preceding details are guideline values established under laboratory conditions. These values are subject to a certain manufacturing tolerance. The data contained in this product information sheet represents Optigrün's technical knowledge at the time of publication. Optigrün reserves the right to change and update details in accordance with new insights and to modify specified properties accordingly. No liability accepted for misprints.

Optigrün international AG

Am Birkenstock 15 – 19,
72505 Krauchenwies-Göggingen
Tel. +49 7576 772-0, Fax +49 7576 772-299, info@optigruen.de

Optigreen Limited (Service UK only)

Suite G5 Albany Chambers, 26 Bridge Road East
Welwyn Garden City (Herts), AL7 1HL
Phone +44 203 5899400, Fax +44 207 1171664, info@optigreen.co.uk

